

## Modern and stylish design for private application

### Application



### Specifications

Artemis IS 7/11			
<b>General</b>	<b>Model Name</b>	Artemis 7kW	Artemis 11kW
<b>Power Input</b>	<b>Input Rating</b>	176~264Vac, 45-65Hz, single-phase	176~264Vac, 45-65Hz, single-phase 373~457Vac, 45-65Hz, three-phase
	<b>Number of Phase/Wire</b>	L+N+PE	L1+L2+L3+N+PE (support single phase input)
	<b>Internal RCD</b>	30mA type A+DC 6mA	30mA type A+DC 6mA
<b>Power Output</b>	<b>Output Power</b>	7kW rated	11kW rated
	<b>Output Current</b>	32A rated	16A rated
	<b>Charging Interface</b>	IEC 62196-2 Type 2 tethered plug	
<b>User Interface &amp; Control</b>	<b>Status Indicators</b>	RGB LED / Digital display screen(TBD)	
	<b>Buttons and Switch</b>	Emergency stop button	
	<b>Card Reader</b>	ISO 14443A/B	
<b>Communication</b>	<b>Network Interface</b>	4G, Ethernet , Wi-Fi , Bluetooth ,PLC(optional)	
	<b>Charging Protocol</b>	OCPP1.6J/OCPP2.0.1 (TBD)	
<b>Environmental</b>	<b>Operating Temperature</b>	-30°C - 55°C	
	<b>Storage Temperature</b>	-40°C- 85°C	
	<b>Humidity</b>	5% - 95% no condensation	
	<b>Altitude</b>	≤ 3000 m	
<b>Mechanical</b>	<b>Ingress Protection</b>	IP55	
	<b>Enclosure Protection</b>	IK10	
	<b>Cooling</b>	Natural cooling	
	<b>Dimension (WxHxD)</b>	282*409*148 mm	282*409*148 mm
	<b>Weight</b>	approx. 4.5kg	approx. 5.6kg
	<b>Connection</b>	Case C (5m Cable)	
	<b>Installation</b>	Wall-mounted, Column-mounted	
<b>Regulation</b>	<b>Certificate / Compliance</b>	IS 17017 / AIS 138	

Note: Pictures are for reference only, please prevail in kind.

+86 400 828 0768  
<http://www.starcharge.com>

