



## Main Features

- Excellent operation efficiency, dual 22 kW output.
- Connect to any backend based on OCPP 1.6J protocol.
- Support 4G, WIFI, Ethernet.
- Space-saving for flexible installation method.



## Specifications

General Information	
<b>Charging Mode</b>	Mode 3 (IEC 61851-1)
<b>Input/Output Power&amp;Current Rating</b>	2 x 22kW/2 x 32A max.
<b>Input/Output Voltage Rating</b>	400Vac±10%, 2*3 phases, 50/60Hz, L1+L2+L3+N+PE
<b>Grid Type</b>	TN-S, TN-C, TN-C-S, TT
<b>Charging Interface</b>	Configuration 01: 1 x IEC 62196-2 Type 2 tethered plug (Case C) Configuration 02: 1 x IEC 62196-2 Type 2 socket (Case B)
<b>Metering</b>	MID meter, Accuracy: Class 1
<b>Internal RCD</b>	Type B
<b>Protection</b>	Overcurrent, Overvoltage, Undervoltage, Residual current, Short circuit, Over temperature, Ground fault, Integrated surge protection
User Interface	
<b>Display &amp; Support Languages</b>	4.3 inches screen
<b>Status Indication</b>	LED strip
<b>Button and Switch</b>	DIP switch inside (Used for setting output current limitation)
<b>User Authentication</b>	RFID card, App, Credit card (optional)
<b>RFID Reader</b>	ISO/IEC 14443 A/B, ISO/IEC 18092, IEC/ISO 15693
Communication	
<b>Network Interface</b>	4G, Wifi, Ethernet
<b>Protocol (EVSE&amp;Backend)</b>	OCPP 1.6J
<b>Protocol (EVSE&amp;EV)</b>	Control pilot (default), ISO 15118 (optional)
Environmental	
<b>Operating Temperature</b>	-25°C to 45°C
<b>Storage Temperature</b>	-40°C to 70°C
<b>Humidity</b>	5% to 95% no condensation
<b>Altitude</b>	≤2000m above sea level
Mechanical	
<b>IP Rating</b>	IP54@Case B, IP55@Case C
<b>IK Rating</b>	IK10
<b>Cooling</b>	Natural cooling
<b>Charging Cable Length</b>	5m
<b>Dimensions (WxHxD)</b>	395*504*197mm
<b>Weight</b>	Approx. 11kg (Case B) Approx.16kg (Case C)
<b>Installation</b>	Wall mounting, Pole mounting (Pole is optional)
Certification and standards	
<b>Standards and compliance</b>	IEC 61851-1, IEC 61851-21-2, LVD 2014/35/EU, RED 2014/53/EU
<b>Certification</b>	CE